iCON 15

Stylish toilet and bathroom ventilation

































KEY FEATURES

- Flow rate up to 19 l/s (69 m³/h)
- Stylish, slim and unobtrusive in walls or ceilings
- Different colour covers available
- Unique iris shutter, prevents backdraughts, operates silently
- Interchangeable control modules match fan to installation requirements
- IPX4 rating
- 3 year warranty

iCON 15 is ideal for toilets, en-suites, shower rooms and bathrooms. Recessed into the wall or ceiling, it is stylish and unobtrusive, even in the smallest of spaces. The circular design means no squaring up is required, adding to the already simple installation procedure.

iCON 15 is designed to provide ventilation levels that comply with the latest Building Regulations. The iCON fan is an efficient, stylish and unique ventilation solution for the modern home. The shutter design makes switching on and off almost silent and helps reduce external noise ingress.

The slim profile and iris shutter of the iCON make it a fan which will blend discreetly into any setting. Two iCON 15 shower kits including (Timer / Humidity Timer) module and ducting installation kits are available.

MODULES



| 72573602 | PCM | Pull cord |
|----------|-------|---------------------------------------|
| 72612601 | ТМ | Timer |
| 72675702 | DTM | Delayed timer with pull cord |
| 72687103 | нтм | Humidity timer with pull cord |
| 72687104 | PRTM | Motion sensor timer |
| 72687102 | PRHTM | Motion sensor with humidity timer |
| 72675703 | 2SHM | 2 speed humidity with pull cord boost |













TECHNICAL DATA

| Specification | iCON 15 | | |
|------------------------------|---------------------|--|--|
| Air flow [m³/h / l/s] | 69 / 19 | | |
| Fan type | axial | | |
| Mounting position | wall / ceiling | | |
| Sound pressure @ 3 m [dB(A)] | 28.8 | | |
| Power [W] | 9.4 | | |
| Building regulations | compliant | | |
| Duct diameter [mm] | 100 | | |
| Supply voltage | 230 V / 1ph / 50 Hz | | |
| Ingress protection rating | IPX4 | | |
| Max ambient temperature [°C] | 40 | | |
| Weight [kg] | 0.74 | | |
| Dimensions H x W x D [mm] | 197 x 197 x 108.5 | | |
| Part number | 72683501 | | |
| EAN | 5019009307633 | | |

COVERS

| Colour | Part No. | Colour | Part No. |
|------------|----------|---------------|----------|
| Silver | 52634504 | Ultimate Grey | 52634514 |
| Sandstone | 52634505 | Turquoise | 52634515 |
| Anthracite | 52634503 | Navy Blue | 52634516 |
| Chrome | 52634502 | | |









Sandstone

Silver

Chrome

Anthracite









Ultimate Grey

Turquoise

Navy Blue

DIMENSIONS






| Model | Α | В | С | D | E |
|---------|-----|-------|------|-----|----|
| ICON 15 | 197 | 108.5 | 67.5 | 100 | 40 |

| SHOWER KIT | | |
|------------|--|--|
| 90000434 | iCON 15, Timer module, flexible ducting | |
| 90000433 | iCON 15, Humidity / Timer module, flexible ducting | |

PERFORMANCE



CONTROLS AND ACCESSORIES





HTM Module No: 72687103 Adjustable humidity setting, adjustable timer and pull cord timer.





PRTM Module No: 72687104

Motion sensor activation with adjustable timer between 1-30 minutes.

Others products available from airflow.com

Call: 01494 525252

Visit: airflow.com

80000796 - Issue 4 12/24



Airflow Developments Limited Aidelle House, Lancaster Road, Cressex Business Park, High Wycombe, Buckinghamshire, United Kingdom, HP12 3QP

E-mail: info@airflow.com Telephone: +44 (0) 1494 525252

airflow.com

© Airflow Developments Limited. Airflow Developments Limited reserve the right, in the interests of continuous development, to alter specifications without prior notice. All orders are accepted subject to our conditions of sale which are available on request

