# iCON 30

Stylish toilet, bathroom and utility room ventilation

































#### **KEY FEATURES**

- Flow rate up to 33 l/s (119 m³/h)
- Stylish, slim and unobtrusive in walls or ceilings
- Different colour covers available
- Unique iris shutter, prevents backdraughts, operates silently
- Interchangeable control modules match fan to installation requirements
- IPX4 rating
- 3 year warranty

iCON 30 is quiet, powerful and designed for recessed or surface mounting in walls or ceilings in larger toilets, bathrooms and utility rooms.

iCON 30 is designed to provide ventilation levels that comply with the latest Building Regulations.

The iCON fan is an efficient, stylish and unique ventilation solution for the modern home. The shutter design makes switching on and off almost silent and helps reduce external noise ingress.

The slim profile and iris shutter of the iCON make it a fan which will blend discreetly into any setting.

## **MODULES**



72573602	PCM	Pull cord
72612601	ТМ	Timer
72675702	DTM	Delayed timer with pull cord
72687103	нтм	Humidity timer with pull cord
72687104	PRTM	Motion sensor timer
72687102	PRHTM	Motion sensor with humidity timer
72675703	2SHM	2 speed humidity with pull cord boost













#### **TECHNICAL DATA**

Specification	iCON 30				
Air flow [m³/h / l/s]	121 / 33				
Fan type	mixed flow				
Mounting position	wall / ceiling				
Sound pressure @ 3 m [dB(A)]	33.3				
Power [W]	10.7				
Building regulations	compliant				
Duct diameter [mm]	100				
Supply voltage	230 V / 1ph / 50 Hz				
Ingress protection rating	IPX4				
Max ambient temperature [°C]	40				
Weight [kg]	1.2				
Dimensions H x W x D [mm]	225 x 225 x 144				
Part number	72687257				
EAN	5019009331195				

### **COVERS**

Colour	Part No.	Colour	Part No.
Silver	52634507	<b>Ultimate Grey</b>	52634517
Sandstone	52634508	Turquoise	52634518
Anthracite	52634506	Navy Blue	52634519







Sandstone

Silver

Anthracite









Ultimate Grey

Turquoise Navy Blue

**DIMENSIONS** 






S

R = Recessed without skirt

Model	Α	В	С	D	E	F	G	Н	1
iCON 30 (R)	225	144	92	97	43	51	20	30	148
iCON 30 (S)	225	144	101	97	-	-	-	29	-

#### **PERFORMANCE**



## **CONTROLS AND ACCESSORIES**





**HTM Module** No: 72687103 Adjustable humidity setting, adjustable timer and pull cord timer.





PRTM Module No: 72687104

Motion sensor activation with adjustable timer between 1-30 minutes.

Others products available from airflow.com

Call: 01494 525252

Visit: airflow.com

80000797 - Issue 4 012/24



**Airflow Developments Limited** Aidelle House, Lancaster Road, Cressex Business Park, High Wycombe, Buckinghamshire, United Kingdom, HP12 3QP

E-mail: info@airflow.com Telephone: +44 (0) 1494 525252

airflow.com

© Airflow Developments Limited. Airflow Developments Limited reserve the right, in the interests of continuous development, to alter specifications without prior notice. All orders are accepted subject to our conditions of sale which are available on request

