

AM120/1120-0005 WRAS

Pre-wall installation system for toilets with bidet function

Application

For mounting in front of a support wall or in to a plasterboard construction
 For floor thickness 0–200 mm
 For installation of wall-hung WC pans with a connecting pitch of 180 mm or 230 mm
 Toilet with bidet function

Features

- Adjustable anchor feet and a spring-lock system, with a range of 0–200 mm
- Visible marks for both leveling and the centerline
- Sliding rail holder for the waste connector can be set to eight positions between 0–93 mm
- Angle valve with the ability to connect to the Mepla piping system
- The frame construction allows the anchoring to a separate sufficiently strong plasterboard partition, in front of the bearing wall
- The installed module is covered with a plasterboard panel and there is no need for any additional fixing or anchoring elements
- The construction of polystyrene insulation prevents condensation forming on the surface of the tank and dampens the vibrations from the tank into the building structure
- Preparation for connecting water from WC cistern to bidet
- Dual flush independently adjustable with hygienic reserve
- Suitable for installation of remote or sensor flushing
- Compatible with all ALCA flush plates
- Maintenance work without using any tools
- Water supply from rear / top / left / right
- The cistern is made of one piece, thus ensuring 100% impermeability
- The service opening cover simplifies assembly and prevents the penetration of moisture and impurities
- Installation depth adjustable from 20–95 mm
- Installation depth 125 mm
- Frame material: powder-coated metal
- Preparation for connecting electricity to bidet ceramics
- Cistern hinges made of two-component material insulate the transmission of vibrations from buildings
- Wall Hung Toilet Frame and Concealed Cistern AM101 certified according to WRAS standard (certificate no. 2206330)

Scope of supply

- Cistern with fill and flush valve
- Self-supporting frame
- Threading 1/2" for water connection with an integrated angle valve 1/2"–3/8"
- Fixation set: screw Ø8x60 – 4 pcs, dowel Ø12 – 4 pcs
- Fixation material for fixing the WC pan: threaded rod M12 – 2 pcs, washers – 4 pcs, cover – 2 pcs, nut – 2 pcs, thread protector – 2 pcs
- Elbow waste connector HT 90/90 polyethylene, PE-HD
- Inlet seal, PP outlet, wrapping seal
- Drainage seal, PP connector, connector seal
- End-caps set for protecting the connecting holes during installation of the system
- The 2 piece cover of the service opening is simply adjustable
- Eccentric reduction HT 90/110 polyethylene, PE-HD
- Set for inserting toilet tablets
- Corrugated flexible pipe with ends for connection to the bidet

Order number, Logistic information

Code	EAN	Weight (piece packing palett)	Dimensions (piece packing)	Quantity (packing palett)
AM120/1120-0005	8595580581688	14,22 14,22 233,3 kg	1130x520x145 1130x520x145 mm	1 15 pcs

Warranty

2/15 years *

Norms

EN 14124, EN 14055

Technical specifications

- Water connection from the back or top via mounting holes G1/2 "
- Functional range of water pressure 0,05–1,0 MPa
- Recommended range of water pressure 0,3–0,5 MPa
- Large flush 6–9 l
- Small flush 2,5–3,5 l
- Factory setting of large flush 6 l
- Factory setting of small flush 3 l
- Hygienic reserve 3 l
- Water volume in the cistern 9 l
- Load test 400 kg

